

Borel Corporation
 110 Ohio Street
 Buffalo, NY 14240
 Contact Information:
 Telephone: 800-888-4910
 Emergency Telephone: 860-571-5100

H.M.I.S.
 HEALTH 3*
 FLAMMABILITY 0
 REACTIVITY 0
 These ratings should be used only
 as part of full implemented
 H.M.I.S. program.

M A T E R I A L S A F E T Y D A T A S H E E T

SECTION 1 - PRODUCT INFORMATION

DATE OF PREPARATION 4/20/07

TRADE NAME..... 1000 SOLVENT PHYSICAL FORM: SOLVENT
 MANUFACTURER CODE I.D. / IDH No. 1080172 (Formerly a Sovereign Specialty Chemical Inc Product)
 SOVEREIGN MANUFACTURER CODE I.D. 185-00031C50

SECTION 2 - HAZARDOUS INGREDIENTS/COMPOSITION INFORMATION

INGREDIENT	% BY WGT	CAS NO.	ALLOWABLE EXPOSURE LEVEL		SARA 313	VP mm Hg @ 20 DEG C		
			PEM MG/CU.M.	SKIN				
METHYLENE CHLORIDE	100	75-09-2	TLV-TWA	50	174	X	350	
			OSHA-PEL	25	87			
			OSHA-STEL	125	437			15 MIN
			LFL	16.0	UFL			66.0

LFL = LOWER FLAMMABILITY LIMIT PERCENT
 UFL = UPPER FLAMMABILITY LIMIT PERCENT
 SKIN = SKIN ABSORPTION MUST BE CONSIDERED AS A ROUTE OF EXPOSURE
 C-CEILING= ALLOW. EXPOSURE LEVEL SHOULD NOT BE EXCEEDED FOR ANY TIME PERIOD
 MRL = MANUFACTURER RECOMMENDED EXPOSURE LIMIT
 = SHORT TERM EXPOSURE LIMIT
 SARA 313 = CHEMICAL IS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313
 OF TITLE III OF S.A.R.A. 40 CFR PART 372

SECTION 3 - HAZARDS IDENTIFICATION

EFFECTS OF SHORT TERM OVEREXPOSURE

SWALLOWING

Can cause gastrointestinal irritation, nausea, and vomiting. Aspiration of material into lung may cause chemical pneumonitis which can be fatal.

INHALATION

Preexisting heart conditions may be aggravated by exposure to Methylene Chloride.

May cause narcotic effects.

Exposure to chlorinated solvents may result in liver and kidney, and heart sensitization.

Overexposure may cause unconsciousness and possible death.

May cause nose or throat irritation. High concentrations may cause acute central nervous system depression characterized by headaches, dizziness, nausea and confusion.

Reduces the blood's oxygen-carrying capacity by the formation of carboxy-hemoglobin. Reduced blood oxygen levels may be harmful to users, especially those with existing heart disease.

EYE

May cause eye irritation.

SKIN

May be absorbed through the skin in harmful amounts.

SECTION 3 - HAZARDS IDENTIFICATION (Continued)

SKIN

May cause severe skin irritation.

EFFECTS OF REPEATED OVEREXPOSURE

Solvent exposure may result in liver and kidney, and heart sensitization.

SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH.

Methylene Chloride has been identified as a potential carcinogen by the International Agency for Research on Cancer (IARC Group 2B - Probable Human Carcinogen) and as a substance "Reasonably Anticipated To Be A Carcinogen" by the National Toxicology program (NTP Group 2). These classifications are based on animal studies (mice & rats) which indicated a dose related incidences in lung, liver and mammary tumors. Human epidemiological studies indicate that the potential carcinogenic effect of methylene chloride is dose dependent. This is supported by the observation of an increased incidence of liver cancer subsequent to high exposure (140 -470 ppm) in a film production plant. Workers in another facility who were exposed to a much lower concentration (26 ppm) showed no increase in cause specific death.

SECTION 4 - FIRST-AID MEASURES

SWALLOWING

If swallowed call Poison Control Center, Hospital Emergency Room, or Physician immediately.

INHALATION

Remove to fresh air immediately. If breathing has stopped, give artificial respiration. Keep warm and quiet. Get medical attention immediately.

EYE

Flush with large amounts of water, lifting upper and lower lids occasionally. Continue for at least 15 minutes. Get medical attention immediately.

SKIN

Remove contaminated clothing. Wash affected area with soap and water. Obtain medical attention if irritation persists.

NOTES TO PHYSICIAN

Do not give stimulants. Epinephrine or ephedrine may adversely affect the heart with fatal results.

SECTION 5 - FIRE-FIGHTING MEASURES

NEPA FLAMMABILITY CLASSIFICATION Not Applicable

FLASHPOINT Not applicable

EXTINGUISHING MEDIA

None should be needed.

UNUSUAL FIRE AND EXPLOSION HAZARDS

This product contains halogenated hydrocarbons; contact with aluminum may cause violent reaction and or explosion. Manufacturer's of Methylene Chloride report no flash point using the TOC, TCC, and COC methods. However, it is known that methylene chloride does have a flammable range 14% (LFL) and 22% (UFL) at 25 deg C. These represent very high concentrations that would present very serious employee exposures relative to OSHA and ACGIH standards. Due to the lack of a typical flashpoint some confusion exists regarding the assignment of HMIS flammability ratings. Some suppliers have suggested that a flammability rating of 1 should be assigned to methylene chloride. Others suggest that the lack of a true flashpoint requires that a zero flammability rating be assigned. Prevent circumstances which would result in methylene chloride concentrations within the flammable range as well as exposure of liquid or vapor to sources of ignition. Please keep in mind that the presence of other flammable substances in this or other product mixtures may alter the flashpoint and increase the flash fire risk and the HMIS flammability rating.

SPECIAL FIRE FIGHTING PROCEDURES

None known

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

The use of a NIOSH/MSHA approved, TC19C, air-supplied breathing apparatus

SECTION 6 - ACCIDENTAL RELEASE MEASURES (Continued)

TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED
may be required. Consult with a qualified occupational health and /or
safety professional.
Refer to Section 8 and don respirators, eye, hand, and body protection
appropriate for the size of the spill and the exposures encountered.

WASTE DISPOSAL

Dispose in accordance with Federal, state and local regulations.

ENVIRONMENTAL HAZARDS

None known

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

None likely to be needed.

OTHER PRECAUTIONS

THIS PRODUCT IS INTENDED TO BE USED ONLY BY THE PROFESSIONAL (INDUSTRIAL)
APPLICATOR UNDER PROPERLY CONTROLLED CONDITIONS. A QUALIFIED OCCUPATIONAL
HEALTH PROFESSIONAL SHOULD EVALUATE EXPOSURES TO THIS PRODUCT.
THE USE OF THIS PRODUCT IN CONFINED AREAS MAY RESULT IN DANGEROUS AIRBORNE
CONCENTRATIONS. THIS MAY CAUSE THE SERIOUS HEALTH EFFECTS DESCRIBED IN
SECTION III OF THIS MSDS.

SECTION 8 - EXPOSURE CONTROLS

RESPIRATORY PROTECTION

Proper selection of respiratory protection depends upon many factors
including duration/level of exposure and conditions of use. In general
exposure to organic chemicals such as those contained in this product may
not require the use of respiratory protection if used in well ventilated
areas. In restricted ventilation areas a NIOSH approved chemical cartridge
respirator may be required. Under certain conditions, such as spraying, a
mechanical prefilter may also be required. In confined areas use a NIOSH/
MSHA approved air supplied respirator. If the TLV's listed in Section II
are exceeded use a properly fitted NIOSH/MSHA approved respirator with an
appropriate protection factor. Refer to OSHA 29 CFR 1910.134 "Respiratory
Protection", and "Respiratory Protection A Manual And Guideline, American
Industrial Hygiene Assoc."

VENTILATION

Provide general dilution and local exhaust ventilation in sufficient volume
and pattern to keep concentrations of hazardous ingredients listed in
Section II below the lowest exposure limit stated. Remove decomposition
products that are generated when welding, cutting, or brazing objects
coated with this product. Refer to "Industrial Ventilation - A Manual of
Recommended Practice " ACGIH .

HAND PROTECTION

Wear appropriate impermeable gloves (North- Silver Shield).

EYE PROTECTION

Wear safety glasses meeting the specifications of ANSI Z87.1 where no
contact with the eye is anticipated. Chemical safety goggles meeting the
specifications of ANSI Z87.1 should be worn whenever there is a possibility
of splashing or other contact with the eyes.

OTHER PROTECTIVE EQUIPMENT

Eyewash facility, safety shower.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE 102 DEG.F. (39 DEG.C.) TO 106 DEG.F.(41 DEG.C.)

VAPOR DENSITY Heavier than air. % VOLATILE BY VOLUME 100

EVAPORATION RATE VOC .00 lb/gal less water& NPRS* 0 g/l less water CALCULATED
Slower than diethyl ether.

WEIGHT LB./GAL. 11.1 VOC .00 lb/gal solids 0 g/l solids CALCULATED
SPECIFIC GRAVITY 1.3

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES (Continued)

All Physical data determined at 68 DEG. F. (20 DEG. C.) 760 mm Hg
* Negligibly Photochemically Reactive Materials

SECTION 10 - STABILITY AND REACTIVITY

STABILITY

Avoid open flames, welding arcs or other high temperature sources which induce thermal decomposition.

CONDITIONS TO AVOID

None known

INCOMPATIBILITY (MATERIALS TO AVOID)

Aluminum

This product contains halogenated hydrocarbons which may react with aluminum. Avoid contact with aluminum in situations in which pressures may be elevated or in which reactions may be enclosed. Do not use spray equipment systems containing aluminum parts.

HAZARDOUS DECOMPOSITION PRODUCTS

Burning, including when heated by welding or cutting, will produce smoke, carbon monoxide and carbon dioxide. In addition, phosgene, formaldehyde, hydrogen chloride, chlorine, may be generated.

HAZARDOUS POLYMERIZATION

Will not occur

CONDITIONS TO AVOID

This product contains halogenated hydrocarbons which may decompose to form hydrogen chloride, chlorine, and phosgene when in contact with hot surfaces, open flames, and U.V. radiation. Do not use this material near welding operations

SECTION 11 - TOXICOLOGICAL INFORMATION

No information available.

SECTION 12 - ECOLOGICAL INFORMATION

No information available.

SECTION 13 - DISPOSAL CONSIDERATIONS

See Section 6.

SECTION 14 - TRANSPORT INFORMATION

ITEM: / IDH No. 1080172	DESC/SIZE: 1000 SOLVENT				
MODE	PROPER SHIPPING NAME	CLASS	I.D.#	PKG	GRP
IATA (ATR)	NAERG: FE-SD RQ ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, NOS (METHYLENE CHLORIDE) NAERG: 9L	9	UN3082	III	
DOT (HM-181) (DOMESTIC SURFACE)	RQ ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, NOS (METHYLENE CHLORIDE) NAERG: 171	9	UN3082	III	
IMDG CODE (OCEAN)	RQ ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, NOS (METHYLENE CHLORIDE)	9	UN3082	III	

SECTION 14 - TRANSPORT INFORMATION (Continued)

/ IDH No. 1080172

DESC/SIZE: 1000 SOLVENT

MODE PROPER SHIPPING NAME CLASS I.D.# PKG GRP

NOTE! The assignment of Proper Shipping Names is in part a function of the size of the product container and the transport mode. For example, the Proper Shipping Name for a bulk container can differ significantly from the Proper Shipping Name for the same product packaged in a non-bulk container. This can also be true for products shipped via different modes of transportation (i.e. ground, air, ocean). The descriptions provided above are intended to provide some guidance. However, these descriptions may not apply to your package size or mode of shipment. The U.S. Code of Federal Regulations, 49 CFR - Transportation, regulations, and the policies established by some transporters, require that the shipper properly classify and assign a Proper Shipping Name, and label, mark and package the material properly. Therefore, the user of this information is cautioned to consult with applicable regulations, and with qualified advisors prior to the repackaging and or reshipment of this or other any product which contain this product.

SECTION 15 - REGULATORY INFORMATION

All ingredients in this product are listed on the US TSCA Inventory.
All ingredients in this product are listed on the Canadian Domestic Substance List.

WARNING: This product contains
METHYLENE CHLORIDE;
a chemical known to the State of California to cause cancer.

INGREDIENT	CAS NO.	DETAIL INVENTORY LIST INFORMATION
METHYLENE CHLORIDE	75-09-2	TSCA(8a CAIR) TSCA(8a PAIR) TSCA(8d) DSL

DETAIL INVENTORY LIST DESCRIPTION

T. /Toxic Substances Control Act
(8a CAIR)Comprehensive Assessment Information Rules
(8a PAIR)Preliminary Assessment Information Rules
(8d)Health and Safety Reporting Rules
DSI./Canadian Domestic Substance List

SECTION 16 - OTHER INFORMATION

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

SECTION 16 - OTHER INFORMATION (Continued)

For Safety and Regulatory Information contact:
Product Safety and Regulatory Affairs,
Rocky Hill, CT
860 571-5204