



POWERHOLD CARPET SEAMING TAPE

MATERIAL SAFETY DATA SHEET

I. PRODUCT IDENTIFICATION

Name: Carpet Seaming Tape
Class: Thermoplastic Carpet Seam Tape
Emergency Telephone CHEMTREC:
800-424-9300

II. HMIS (0=minimal hazard; 4= severe)
Health = 0 Flammability = 1 Reactivity = 0

III. HAZARDOUS INGREDIENTS

None per OSHA Regulation: 29CFR1910.1200 None per SARA Title III, Section 313 and TSCA 40 CRF 372

IV. PHYSICAL DATA

MELTING POINT: 230°F; BOILING POINT: Not established;
ODOR: Neutral; SPECIFIC GRAVITY: 0.98; VAPOR PRESSURE:
Not established; VAPOR DENSITY: Not established
No VOC at ambient temperature.

V. FIRE & EXPLOSION HAZARD DATA

FLASH POINT: NA; AUTOIGNITION TEMPERATURE: Not established; LOWER EXPLOSIVE LIMIT: Not established; UPPER EXPLOSIVE LIMIT: Not established; EXTINGUISHING MEDIA: A solid stream of water may scatter molten product. UNUSUAL FIRE AND EXPLOSION HAZARDS: Material will burn in a fire. SPECIAL FIRE FIGHTING PROCEDURES: Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, Carbon monoxide

VI. HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: Inhalation, Ingestion, skin and eye contact. EFFECTS OF OVEREXPOSURE: Eyes - No irritation hazard in normal industrial use. Exposure to hot material may cause thermal burns. Skin - Skin contact at room temperature is not irritating. Contact with product at elevated temperatures can result in thermal burns. Inhalation - No irritation hazard in normal industrial use. Ingestion - Ingestion is not an anticipated route of exposure

VII. FIRST AID MEASURES

EYE CONTACT: Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush eye with water for 15 minutes. Get medical attention. SKIN CONTACT: Wash affected area(s) thoroughly with soap and water. For hot material, immediately immerse in or flush the affected area with large amounts of cold water to dissipate heat. Cover with clean gauze and do not attempt to remove the material yourself. Seek medical attention. Medical personnel: coat with mineral oil to soften material for removal. INHALATION: This material does not present a hazard if inhaled. Remove to fresh air if neces-

sary. INGESTION: No hazard in normal industrial use. Do not induce vomiting. Seek medical attention if symptoms develop.

VIII. SPILL OR LEAK PROCEDURES

SPECIAL PROTECTION: No adverse health effects expected from the clean-up of spilled material. CLEAN-UP: Allow molten material to solidify before disposal.

IX. PROTECTIVE EQUIPMENT

No safety equipment required other than goggles.

X. SPECIAL PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN

The Floor Covering Distributor Alliance believes the data set forth herein is accurate as of the date hereof, and makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.



POWERHOLD 100 CARPET PAD CEMENT

MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT IDENTIFICATION

Manufactured for: Floor Covering Distributor Alliance
Emergency Phone: 800-535-5053
Generic ID: Neoprene Rubber Adhesive in Solvent Solution
DOT Hazard Classification: None
Product Identity: POWERHOLD 100 Carpet Pad Cement

SECTION II - HAZARDOUS COMPONENTS

	% (weight)	PEL	TLV
Hexane (CAS# 110-54-3)	35	500 ppm	50 ppm
Lacelene (CAS# 64742-89-8)	24	400 ppm	400 ppm
Methyl Ethyl Ketone (CAS# 78-93-3)	8	300 ppm	200 ppm

SARA TITLE III Reportable: Methyl Ethyl Ketone and n-Hexane Lacelene

SECTION III - PHYSICAL DATA

Initial Boiling Point: 149°F. Vapor Pressure: 125.0 mm Hg @ 68°F. Vapor Density (Air=1.0): 3.0. Specific Gravity: 0.77.
Percent Volatiles: 70.4%. G/L VOC (Calculated): 542.0.

SECTION IV - FIRE AND EXPLOSION DATA

Flash Point: <0°F. Explosive Limit (Product): 1.2% . Extinguishing Media: Foam, CO2, Dry Chemical. HAZARDOUS DECOMPOSITION PRODUCTS: May form toxic materials: carbon dioxide and carbon monoxide, hydrogen chloride, phosgene, various hydrocarbons, etc. SPECIAL FIRE FIGHTING PROCEDURES: Water may be used to keep fire-exposed containers cool until fire is out. Wear self contained breathing apparatus with full facepiece operated in pressure-demand or other positive pressure mode when fighting fires. UNUSUAL FIRE & EXPLOSION HAZARDS: Never use welding or cutting torch on or near cans (even empty) because resultant pressure could rupture. Empty cans should be incinerated.

SECTION V - HEALTH HAZARD DATA

Permissible Exposure Level: 300 ppm. Threshold Limit Value: 50 ppm. EFFECTS OF EXPOSURE: Eyes- Can cause irritation, redness, tearing, blurred vision. Skin- Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis. Breathing- Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, and even asphyxiation. First Aid: Skin- Soap and water Eyes- Flush with water, lifting upper and lower lids occasionally. Ingestion- Do not induce vomiting. Call physician or transport to an emergency facility. Inhalation- If affected, remove individual to fresh air. Use only in well ventilated areas

SECTION VI - REACTIVITY DATA

Stability: Stable. Incompatibility: None. Hazardous Decomposition: None. Hazardous Polymerization: Cannot Occur. Conditions To Avoid: Extreme Heat. Open Flames.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb liquid on paper, vermiculite, floor absorbent, or other absorbent material and transfer to hood. Allow volatile portion to evaporate in hood. Allow sufficient time for vapors to completely clear hood duct work. Dispose of remaining material in accordance with applicable regulations.

SECTION VIII - PROTECTIVE EQUIPMENT

VENTILATION: Adequate ventilation is essential to prevent vapor build-up. Open all available windows and entrances to insure good ventilation. RESPIRATOR PROTECTION: Adequate ventilation is normally sufficient. If eyes begin to water or dizziness or headaches are experienced, increase fresh air supply, wear an NIOSH approved respirator, or leave the area. PROTECTIVE GLOVES: Wear protective gloves to prevent skin contact. EYE PROTECTION: Wear glasses or protective goggles to avoid splashes. OTHER PROTECTIVE EQUIPMENT: None required. WASH HANDS THOROUGHLY WITH SOAP AND WATER.

SECTION IX - SPECIAL PRECAUTIONS

Protect from freezing. Use only in applications as stated on the label. Do not take internally. Close container after each use. Avoid skin and eye contact.

Ventilation with fresh air, including open doors and windows should be observed during any flooring installation. Operate HVAC systems at 100% fresh air intake before, during and after installation to eliminate lingering odors or particulate matter. KEEP OUT OF REACH OF CHILDREN.

The Floor Covering Distributor Alliance believes the data set forth herein is accurate as of the date hereof, and makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.

Original March 2004