

=====I. PRODUCT IDENTIFICATION=====

Trade Name: Roberts Capitol 017 Latex Seaming Adhesive

Chemical names, common names: Natural Latex Seaming Adhesive

Manufactured by: Roberts Capitol, Inc.  
Address: 300 Cross Plains Blvd.  
Dalton, GA 30721

Emergency Phone: 800-424-9300 (Chemtrec)  
Business Phone: 706-277-5294

Date revised: 06/21/10  
By: M. King

HMIS Rating: H = 1 F = 0 R = 0

=====II. HAZARDOUS INGREDIENTS=====

	<u>CAS No.</u>	<u>% by wt.</u>	<u>PEL</u>	<u>TLV</u>
Ammonia	7664-41-7	1-3	ND	25 ppm

Reportable hazardous chemicals for SARA TITLE III Section 311, 312, 313:

None

=====III. PHYSICAL PROPERTIES =====

Vapor Density (Air=1): Greater than 1	Boiling Point: 212F
Solubility in Water: Miscible	Specific gravity: 0.96
Vapor Pressure (mmHg at 20c): Same as water	pH: 10.5 - 10.9
Evaporation rate (nBuAc=1): Same as water	

Appearance & odor: White, thick liquid with slight ammonia odor.

Percent Volatile: 36 - 38% by weight (water)

VOC calculated (Coating) VOC: 0 grams/liter

=====IV. FIRE AND EXPLOSION=====

Flash point, Pensky-Martens C.C: NA  
Auto-Ignition Temperature, F: NA  
Flammable limits in air, Volume %: Lower: Not Applicable Upper: NA  
Fire Extinguishing Materials:

- Water Spray       Carbon Dioxide       Other:
- Foam                       Dry Chemical

Special Fire fighting Procedures: Wear self-contained breathing apparatus.

Unusual Fire and Explosion Hazards: None known

=====

===== V. HEALTH HAZARD INFORMATION =====

SYMPTOMS OF OVEREXPOSURE

Inhalation: May cause slight irritation to upper respiratory tract.

Eyes: May cause slight irritation.

Skin: None known; may cause slight irritation.

Ingestion: Not a likely route of entry under proper handling conditions.  
May cause vomiting. Symptoms may be the same as inhalation.

-----  
HEALTH EFFECTS OR RISKS FROM EXPOSURE

Acute: May cause mild skin irritation, irritation of respiratory tract.

Chronic: None known.

While none are known directly associated with this product, note that NIOSH published an alert (no. 97-1375, June 1997) that reported workers exposed to products containing natural rubber latex may develop allergic reactions such as skin rashes; hives; nasal, eye, or sinus symptoms; asthma; and (rarely) shock.

While none are known directly associated with this product, note that NIOSH published an alert (no. 97-1375, June 1997) that reported workers exposed to products containing natural rubber latex may develop allergic reactions such as skin rashes; hives; nasal, eye, or sinus symptoms; asthma; and (rarely) shock.

-----  
FIRST AID: EMERGENCY PROCEDURES

Eye contact: Flush with water for at least 15 minutes. If irritation persists, seek medical attention.

Skin contact: Wash with soap and water. If irritation persists, see a physician.

Inhalation: Remove to fresh air, administer oxygen and if necessary, seek medical attention.

Ingestion: Not a likely route of entry under proper handling conditions. Seek medical attention if necessary.  
-----

SUSPECTED CANCER AGENT?

NO: X

YES: \_\_\_\_\_ Federal OSHA      \_\_\_\_\_ NTP      \_\_\_\_\_ IARC      \_\_\_\_\_ Cal/OSHA

-2-

MSDS --  
Page 3

-----  
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None Known

=====VI. REACTIVITY DATA=====

Stability: X Stable      \_\_\_\_\_ Unstable

Conditions to Avoid: Protect from freezing.

Incompatibility (Materials to Avoid): Oxidizing materials

Hazardous Decomposition Products (including combustion products):

Oxides of carbon, water and organic compounds of unknown structure.

Hazardous Polymerization: Does not occur

Conditions to Avoid: Protect from Freezing.

=====VII. SPECIAL HANDLING INFORMATION=====

Ventilation and Engineering Controls: Use local exhaust. Do not use closed air circulating system. Open windows and doors, if necessary.

Respiratory Protection: Normally none required. Use product in a well ventilated area. Use NIOSH approved respirator if irritation to respiratory tract. If vapors or mists are generated, wear NIOSH/MSHA approved ammonia cartridge vapor/mist respirator.

Eye Protection: Chemical goggles or face shield. Gloves: Chemical resistant gloves.

Other clothing and Equipment: If clothing becomes contaminated, remove and clean before re-wearing.

Work Practices, Hygienic Practices: Follow all label instructions.

Protective Measures During Maintenance of Contaminated Equipment:

Use goggles and gloves when cleaning adhesive from equipment.  
Maintain proper ventilation.

MSDS --  
Page 4

=====**VIII. SPILL, LEAK, AND DISPOSAL PROCEDURES**=====

Keep out of sewer systems to prevent blockage due to polymer deposits.  
Soak up material with absorbent material (sand, sawdust) and place into  
closed containers for disposal.

*Note: Dispose of all wastes in accordance with Federal, State and Local  
regulations.*

=====**IX. Storage & Handling DATA**=====

Other Handling and Storage requirements: Protect against physical damage.  
Store in a cool, dry place (50F - 90F). Keep away from excessive  
heat. Protect from freezing. Shake before using.

=====**X. Regulatory Information** =====

Hazardous Waste 40CFR261: NO Hazardous Waste Number:

Hazardous Substance Superfund: NO RQ(lbs):

All components are in TSCA inventory.

=====**XI. SHIPPING DATA**=====

D.O.T. Proper Shipping Name (49CFR172.101-102): None.

Hazardous Substance (49CFR CERCLA list): No. RQ: N/A

D.O.T. Hazard Classification (49CFR 172.101-102):  
Primary: None Secondary: None.

D.O.T. Labels Required (49CFR172.101-102): None.

D.O.T. Placards Required (CFR172.504): None.

Poison Constituent (49CFR172.203(K)): None.

Bill of Lading Description: Adhesive, NOS

UN/NA Code: N/A

Roberts Capitol, Inc. believes the data set forth herein are accurate as of the date hereof, and makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.